



PARKSIDE decking is perfect in any decking application. It adds beauty, richness and depth to any commercial or residential application.



PARKSIDE TIMBER

Introduction

Parkside Timber has been producing hardwood products for Australians for over 60 years. The natural durability of the species produced plus the high manufacturing standards we uphold means our products are among the highest quality in the marketplace.

Key Benefits

- Parkside products are grown in Australia and produced and manufactured for Australian conditions.
- Parkside Decking heartwood is naturally insect and decay resistant while every piece is treated with an ACQ H3 treatment, ensuring any sapwood that is used is also fully durable.
- Parkside have some of the highest standards and best quality sawmilling technology in the Southern Hemisphere, meaning the quality is second to none. .
- Parkside Decking products are all durability Class 1 above ground species, giving you peace of mind your product will hold its integrity for over 40 years!
- Parkside is Australia's largest producer of Spotted Gum products, so you'll enjoy knowing you're ordering from the Spotted Gum Specialists!
- Parkside Decking is certified by internationally recognised PEFC, denoting that all products are sourced from sustainably managed forests. These values ensure that Australia's forests and Parkside Timber will be around for generations to come.

Commercial and Structural

Parkside Decking can be used in the construction of timber decks, boardwalks, bridges and jetties, as well as a vast array of other platform and structural applications. Commercial decking is available in large section sizes in dressed or rough sawn and features the highest strength group rating for superior span capacity.

All Parkside Decking timbers are manufactured to Australian Standards AS 2796.

Warranty

When correctly installed and maintained, Parkside Timber is guaranteed to perform its intended function for the design life of that component. The terms of warranty will be provided with products when they are supplied. Refer to Parkside Decking Installation Guide for handling, storage, installation and maintenance.

For further information please contact Parkside Timber on freecall 1800 257 099 or timber@parkside.biz.

Please note: Colour variations within timber species in normal photography are only indicative of the colour range.



Species

Spotted Gum

Hardness 11



Grey and Red Ironbark

Hardness 14




Queensland Reds

Hardness 12



Mixed Blends

Hardness 10.5



Hardness refers to the Janka rating which is the hardness level given to each species. The higher the number, the greater the hardness.



Grades

Select | Standard | Feature



Sizes and Lengths

65 | 86 | 135 x 19mm, 135 x 32mm and 140 x 25mm

Lengths: Random packs - 1.5m to 5.7m



Durability

Class 1 Above ground product

ACQ H3 Treatment



Certification

Manufactured to comply with AS 2796

Fire rated in accordance with AS 3959-2009 and BAL 19 as a minimum

Spotted Gum and Red Ironbark are fire rated to BAL 29

Chain of Custody as per AS 4707-2008 PEFC / AFS